Technical Data Sheet

Hometown Series

Iberia Plant



Product Name	Swatch	Size	Standard	Durability Class (Grade)	Dimensional Variation (Type)	Compressive Strength (psi)	24-hr Cold Water Absorption (%)	5-hr Boil Absorption (%)	IRA (g/min per 30in ²)	Core Volume (%)
Albany		Modular	ASTM C216	sw	FBS	>3,000	<6	<10	⊲0	uncored
Augusta		Modular	ASTM C216	sw	FBS	>3,000	<6	<10	⊲30	uncored
Canton		Modular	ASTM C216	sw	FBS	>3,000	<6	<10	⊲30	uncored
Covington		Modular	ASTM C216	sw	FBS	>3,000	<6	<10	⊲0	uncored
Jamestown		Modular	ASTM C216	sw	FBS	>3,000	<6	<10	⊲0	uncored
Windham	THE IS NOT	Modular	ASTM C216	sw	FBS	>3,000	<6	<10	⊲30	uncored

This data represents average results. If specific test results are required, sample should be taken from current production lots. U.S. STANDARD TEST METHODS (ASTM C67) ARE USED AS APPLICABLE, UNLESS OTHERWISE NOTED.

Size	Width	Height	Length	Weight	Brick per Cube	Brick per Sq Ft
Modular	3-1/2"	2-1/4"	7-5/8"	4.7	525	6.86