## **Technical Data Sheet**

## La Paloma Series

International (Spain)



Product Name	Swatch	Size	Standard	Durability Class (Grade)	Dimensional Variation (Type)	Compressive Strength (psi)	24-hr Cold Water Absomtion (%)	5-hr Boil Absorption (%)	IRA (g/min per 30in <sup>2</sup> )	Core Volume (%)
Azul		Modular	ASTM C216	SW	FBX	>5,000	<6	<10	<20	<25
Caste II an a		Modular	ASTM C216	sw	FBX	>5,000	<8	<10	⊲30	<b>⊘</b> 5
Romero		Modular	ASTM C216	sw	FBX	>10,000	<6	<10	<10	<25

This data represents average results. If specific test results are required, sample should be taken from current production lots. U.S. STANDARD TEST METHODS (ASTM C67) ARE USED AS APPLICABLE, UNLESS OTHERWISE NOTED.

Size	Width	Height	Length	Weight	Brick per Cube	Brick per Sq Ft			
Modular	3-5/8"	2-1/4"	7-5/8"	3.9	680	6.75			
Note: products are also available as Thin Brick, see Thin Brick Technical Data Sheet.									

## **Technical Data Sheet**

La Paloma Series -- Thin Brick

International (Spain)



Product Name	Swatch	Size	Standard	Durability Class (Grade)	Dimensional Variation (Type)	Compressive Strength (psi)	24-hr Cold Water Absorption (%)	5-hr Boil Absorption (%)	IRA (g/min per 30in <sup>2</sup> )	Core Volume (%)
Azul Thin Brick		Modular	ASTM C1088	Exterior	твх	N/A	<6	<10	N/A	N/A
Castellana Thin Brick		Modular	ASTM C1088	Exterior	ТВХ	N/A	<10	<17	N/A	N/A
Romero Thin Brick		Modular	ASTM C1088	Exterior	твх	N/A	<6	<10	N/A	N/A

This data represents average results. If specific test results are required, sample should be taken from current production lots. U.S. STANDARD TEST METHODS (ASTM C67) ARE USED AS APPLICABLE, UNLESS OTHERWISE NOTED.

Size	Width	Height	Length	Weight	Brick per Pack	Brick per Sq Ft			
Modular Thin Brick Fla	t 3/4"	2-1/4"	7-5/8"	1.1	36	6.75			
Modular Thin Brick Com	er 3-5/8"	2-1/4"	7-5/8"	0.8	30	4.5/LF			
Note: products are also available as Full Brick, see Full Brick Technical Data Sheet.									